



## Spec Sheet: GE 63A Safeclip Fuse Fittings

- Self cleaning, self aligning base contacts.
- Clip-in fuse links, no tools required for fuse replacement.
- Full shrouded contacts, IP20 degree of protection.
- DIN rail mounting with easy to remove carrier.
- Base made from Phenolic, carrier made from thermoplastic.



### Standards

Australian Standard AS60269 and BS88 Part 6, ASTA, CSA.

### Range

<i>Rated current (Ie)</i>	63A
<i>Rated voltage (Ue)</i>	550V
<i>Rated peak withstand current</i>	80kA
<i>Rated impulse withstand voltage (Uimp)</i>	8kV
<i>Screw mounting size (all)</i>	M5
<i>Weight 1P (Front wire)</i>	0.2kg
<i>Max Cable Size (front / rear)</i>	25mm <sup>2</sup>
<i>Maximum tightening torque (front)</i>	2.5-3Nm
<i>Fuse type (suit all)</i>	ES_

Rated Current (A)	Type of Connection	Colour	Pack Quantity	Catalogue Number
63A	Front Wire Base	Black	10	SC63H-D
	Busbar / Front wire	Black		SC63BH
	2 Stud rear	Black		SC63P
	Front Wire Base	White		SC63H-DWH
	Solid Neutral Link – suit white base	-		ESCLINK
-	Protective Boot – suit rear stud	Black		RS20/32S

### Dimensions

