

W66 INDUSTRIAL SWITCHGEAR

Features:

- IP66.
- Round pin - 1 x M32, 2 x M25 entries.
- Flat pin - 1 x M25, 2 x M20 entries.
- Stainless steel fixings.
- Fully tested & approved.



W66SS310



W66SS550



W66SS332

Features:

- W66B1 base 2 x M25, 1 x M32 entries.
- Padlockable.
- Stainless steel fixings.
- IP66.



W66IS220

SINGLE PHASE SWITCHED OUTLETS

Voltage Rating	Current Rating	Pins No	Pins type	Max Cable mm ²	Part No.
250	10	3	Flat	6	W66SS310
	15				W66SS315
	20				W66SS320F
250	20	3	Round	6	W66SS320
	32			16	W66SS332

THREE PHASE SWITCHED OUTLETS

Voltage Rating	Current Rating	Pins No	Pins type	Max Cable mm ²	Part No.
500	10	4	Round	6	W66SS410
	20			16	W66SS420
	32				W66SS432
	40				W66SS440
	50				W66SS450
500	10	5	Round	6	W66SS510
	20			16	W66SS520
	32				W66SS532
	40				W66SS540
	50				W66SS550



MOTOR RATED ISOLATORS

Voltage Rating	Current Rating	Poles	Max Cable mm ²	Base inc.	Part No.
250	20	2	16	N	W66IS220LB
250	20	2		Y	W66IS220
500	20	3	16	Y	W66IS320
500	32	3	16	N	W66IS332LB
500	32	3		Y	W66IS332
500	63	3	25	N	W66IS363LB
500	63	3		Y	W66IS363

use W66B1 if a base is required (when using LB versions)