



Super M , Motor driven siren 240V AC/DC, 127dB @ 1 metre, 1680 Hz, 1 metre pre wired cable

- Motor driven sirens in various frame sizes, mounting, IP and colours to suit your application.
- Options of constant frequency output (900Hz, 1600Hz, 1800Hz) dependent on model, to most effectively overcome background/ambient noise.
- Available in single or three phase with dB output from 103dB to 145dB, ideal for wide area emergency signalling applications.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Operating Current Type	AC / DC
Operating Voltage	240
Sound Frequency	1680
Sound output	127
Sound Type	Continuous
Material	ABS (Acrylonitrile Butadiene Styrene)
Operating temperature, min	-30
Operating temperature, max	45

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

Catalogue No: **KLXSM240**

MOTOR DRIVEN SIREN SUPER M 127dB 240VACDC 1680Hz

Signalling Devices > Sound Indication > Sirens > Wide Area Sirens - Motor Driven > Super M

