

MG Series – Metal Cable Gland (Stainless Steel)

- 316 Marine Grade Stainless Steel Cable Glands (also available in Nickel Plated Brass)
- Precision engineered from 316 Stainless steel designed for use in weatherproof and harsh environments.
- Ideal for installation in Marine / Offshore environments, Food, Beverage and Pharmaceutical industries

Product Details:

Temperature range - -40°C Min to + 110°C Max (Short term: 120°C)

- 316 marine grade stainless steel

Nylon PA6 cable claw

- Nitrile Butadiene Rubber (NBR) seal and O-ring

IP Protection - IP66 / IP67 / IP68 Note 1

Characteristics - Multi-part component fitting

- NBR Sealing washer and locknut are supplied with this fitting



| Product Catalogue No. | Description | Metric Thread Dimensions | Clamping Range (mm) | Thread Length (mm) |
|-----------------------|---------------------------------|-----------------------------|------------------------|--------------------|
| MGSS-12 | 316 Stainless Steel Cable Gland | M12 X 1.5 | 2.5 - 6 | 10 |
| MGSS-16 | 316 Stainless Steel Cable Gland | M16 X 1.5 | 6 - 10 | 10 |
| MGSS-20 | 316 Stainless Steel Cable Gland | M20 X 1.5 | 9 - 14 | 10 |
| MGSS-25 | 316 Stainless Steel Cable Gland | M25 X 1.5 | 14 - 18 | 12 |
| MGSS-32 | 316 Stainless Steel Cable Gland | M32 X 1.5 | 18 - 25 | 12 |
| MGSS-40 | 316 Stainless Steel Cable Gland | M40 X 1.5 | 24 - 31 | 12 |
| MGSS-50 | 316 Stainless Steel Cable Gland | M50 X 1.5 | 31 - 41 | 12 |
| MGSS-63 | 316 Stainless Steel Cable Gland | M63 X 1.5 | 35 - 45 | 12 |

Note:

1. To achieve the stated IP protection rating, the supplied thread sealing washer must be installed.