

# **PRODUCT DATASHEET** ST PIN 30 2.6 W/827 G9 CL

# LED STAR PIN G9 | Special LED lamps



# **AREAS OF APPLICATION**

- Atmospheric accent lighting throughout the home

#### **PRODUCT BENEFITS**

- Long lifetime of up to 15,000 h
- Very low energy consumption
- Ideal for decorative and free-burning applications

#### **PRODUCT FEATURES**

- LED alternative to conventional high voltage lamps
- Mercury-free lamps



# **TECHNICAL DATA**

# Electrical data

| Rated wattage                          | 2.60 W   |
|--|----------|
| Nominal wattage                        | 2.60 W   |
| Nominal voltage                        | 220240 V |
| Operating frequency                    | 5060 Hz  |
| Power factor λ                         | 0.40     |
| Claimed equiv. conventional lamp power | 30 W     |

# Photometrical data

| Nominal luminous flux                   | 320 lm     |
|---|------------|
| Rated luminous flux                     | 320 lm     |
| Rated color temperature                 | 2700 К     |
| Color rendering index Ra                | ≥80        |
| Lumen main.fact.at end of nom.life time | 0.70       |
| Light color (designation)               | Warm White |
| Standard deviation of color matching    | ≤6 sdcm    |

# Light technical data

| Warm-up time (60 %) | < 0.50 s |  |
|---------------------|----------|--|
| Starting time       | < 0.5 s  |  |

# Dimensions & weight



| Overall length | 52.0 mm |
|----------------|---------|
| Diameter       | 15.0 mm |
| Outer bulb     | T15     |
| Length         | 52.0 mm |

# Temperatures & operating conditions

| Maximum temperature at tc test point | 88 °C |
|--------------------------------------|-------|
|--------------------------------------|-------|

#### Lifespan

| Nominal lamp life time                   | 15000 h |
|--|---------|
| Rated lamp life time                     | 15000 h |
| Number of switching cycles               | 100000  |
| Lumen maintenance at end of service life | 0.70    |

#### Additional product data

| Base (standard designation) | G9     |
|-----------------------------|--------|
| Mercury content             | 0.0 mg |
| Mercury-free                | Yes    |
| Design / version            | Clear  |
| Show WEEE picto             | Yes    |

#### Capabilities

#### Certificates & standards

| Energy efficiency class | A++         |
|-------------------------|-------------|
| Energy consumption      | 3 kWh/1000h |

#### Country-specific categorizations

| ILCOS           | DRT/C-2,6/827-220-240-G9-15/52 |  |
|-----------------|--------------------------------|--|
| Order reference | LEDSPIN30 CL 2,                |  |

#### LOGISTICAL DATA

| Product code  | Product description          | Packaging unit<br>(Pieces/Unit) | Dimensions (length x<br>width x height) | Volume               | Gross weight |
|---------------|------------------------------|---------------------------------|---|----------------------|--------------|
| 4058075812055 | ST PIN 30 2.6 W/827<br>G9 CL | Shipping carton box<br>9        | 345 mm x 153 mm x<br>136 mm             | 7.18 dm <sup>3</sup> | 329.00 g     |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **REFERENCES / LINKS**

For further products and actual information concerning LED lamps see

www.ledvance.com/ledlamps

For Guarantee see

www.ledvance.com/guarantee

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.