

PRODUCT DATASHEETLED VALUE PANEL 300 x 1200 36 W 4000 K

LED VALUE PANEL | LED panel with high efficency and long life



AREAS OF APPLICATION

- Hospitals
- Office areas
- Public areas
- Retail

PRODUCT BENEFITS

- Easy and quick installation
- Easy and quick series connection thanks to simple plug system
- Easy buit-in system for fast connection
- Easy installation with fast connection
- Elegant homogenous design
- Energy saving thanks to LED technology
- Homogeneous light output
- Slim and sleek design

PRODUCT FEATURES

- Ambient temperature in operation: -10...+45 °C
- Average lifespan: 50,000 h
- High luminous efficacy: 90 lm/W
- Lifetime: up to 50,000 h



TECHNICAL DATA

Electrical data

Nominal wattage	36.00 W
Operating mode	External LED driver
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 K
Color rendering index Ra	≥80
Luminous flux	3200 lm
Luminous efficacy	90 lm/W

Light technical data

Beam angle	120 °

Dimensions & weight

Length	1195 mm
Width	295.0 mm
Height	34.0 mm
Product weight	2100.00 g

Colors & materials

Product color	White
Housing color	White
Body material	Aluminum

Lifespan

Lifespan L70/B50 at 25 °C	50000 h

Additional product data

Mounting type	Recessed/Suspended/Surface
Mounting location	Ceiling

Capabilities

Dimmable	No
LED module replaceable	Not replaceable

Certificates & standards

Type of protection	IP20
--------------------	------

Protection class	11

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075330696	Folding carton box 1	1245 mm x 38 mm x 300 mm	2802.00 g	14.19 dm³
4058075330702	Shipping carton box 5	1320 mm x 210 mm x 380 mm	15610.00 g	105.34 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.