Data Sheet





CAT NO. **643085**



Cat No	643085
Colour	White
Туре	Photoelectric
Diameter	147mm
Depth	49mm
Mounting centre	84mm
Siren sound level	85db at 3m
Supply voltage	230-240V a.c. 50Hz

Data Sheet

Professional Photoelectric Smoke Alarm, 240V



CAT NO. **643085**



Product specifications		
Cat No	643085	Quantity
Single Barcode	9321001433958	1
Inner Barcode	9321001433965	6
Outer Barcode	9321001433972	24

Photoelectric

Photoelectric smoke alarms 'see' the smoke. They detect visible particles of combustion, eg smouldering cigarette smoke. They respond to a wide range of fires, but they are particularly responsive to smouldering fires and the dense smoke given off by foam filled furnishings or overheated PVC wiring. This is the technology recommended by fire authorities for residential applications.

Advantages

- Self calibration capacity
- Mesh covering surrounding the chamber to reduce the penetration of smaller dust particles
- Protective installation covering
- Good for smouldering fires and dense smoke
- Not as prone to cooking nuisance alarms as ionisation alarms
- Contain no radioactive material
- Suitable for general use
- Interconnectable up to 20 units
- Surface mounting for easy fit-off

- Power and alarm indicator
- Easy access for wiring
- Hush/Test button
- 9V battery back-up included
- Low battery indication (audio and visual)
- Smoke detector interface (643086) available separately to interconnect with other appliances, circuits and systems e.g. lighting and exhaust fans



Self calibration capacity



New mesh covering surrounding the chamber



Dust protection bag included

Legrand Australia 1300 369 777 www.legrand.com.au ABN 31 000 102 661

Legrand New Zealand 0800 476 009 www.legrand.co.nz Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.