

General Purpose Plastic Enclosures IP66 ABS

The ABS blend plastic material has a wide temperature range and is UV resistant, offering confidence across a range of exterior applications.

Specifications

Material Body: PC and ABS Blend Plastic
Colour: RAL 7035 Grey
Gasket: EPDM Rubber

Temperature Range -15° to +60°C

Glow Wire Test 650°C

UV Resistant Yes

Halogen Free Yes

Environment Protection IP66

Impact Resistance IK06

Part No.	Internal Dimensions (mm)			Lid Screw Type	Lid Colour
	Height	Width	Depth		
005PLC2	100	100	50	Stainless Steel	Opaque
007PL	125	75	50	Stainless Steel	Opaque
006PLC2	100	100	65	Stainless Steel	Opaque
008PLC2	150	110	70	Stainless Steel	Opaque
009APLC2	190	140	75	Nylon	Opaque
010APLC2	240	190	90	Nylon	Opaque
012APLC2	300	220	120	Nylon	Opaque
009CAG	190	145	135	Stainless Steel	Opaque
010CAGC2	243	190	155	Stainless Steel	Opaque
012CAGC2	310	230	160	Stainless Steel	Opaque
008PKC2	150	110	70	Stainless Steel	Clear
009APKC2	190	140	75	Nylon	Clear
010APKC2	240	190	90	Nylon	Clear
012APKC2	300	220	120	Nylon	Clear
009CAK	190	145	135	Stainless Steel	Clear
010CAKC2	243	190	155	Stainless Steel	Clear
012CAKC2	310	230	160	Stainless Steel	Clear



005PLC2



009APLC2



009CAG



010APKC2



009CAK