

For the Best

TERRA Amplifiers “NEW RANGE” Suitable for Apartment Applications

10MM-AS39 Two Output Apartment Amplifier



10MM-AS38 Four Output Apartment Amplifier



Features:

- Built in adjustable gain regulators
- Die cast housing inside plastic heavy duty casing
- Built in power supply source

Technical Data		10MM-AS39	10MM-AS38
Forward Path	Frequency range	47-862 MHz	47-862 MHz
	Outputs	2	4
	Gain	20dB	20dB
	Gain adjustment	0 ÷ - 12dB	0 ÷ - 16dB
	Max output level IMD3=60 dB (DIN45004B)	100 dBµV	100 dBµV*
	Input and Output return loss	>10dB	>10dB
	Noise figure	<6dB	<5dB
	Test point attenuation	-	-20dB
	Port to port output isolation	>16dB	>16dB
	General	Power consumption	230V ~ 50 Hz 3W
Operating temperature range		-20° ÷ +50 °C	-20° ÷ +50 °C
Dimensions & Weight		133x63x39mm / 0.36kg	133x73x39mm / 0.36kg

For more information call:

• **AUST TOLL FREE: 1800 - AERIAL** • **NZ TOLL FREE: 0800 - AERIAL** •
www.matchmaster.com.au