

FD-108 Break Glass Call Point



- Single pole change over contact
- Choice of five colours
- Supplied with test key
- Coated glass element
- Optional transparent flap



Specifications:

Switch action:	Single pole change over
Contact rating (A):	250VAC 10A 24VDC 10A 48VDC 3A
Protection:	IP42
Temp range (°C):	-25 to +55
Cable entry:	3 x 20mm
Terminal Capacity:	6 x 2.5mm ²
Construction:	High impact ABS
Dimensions (w x h x d):	86 x 86 x 56mm
Weight:	200g

Order Code	Description
MBFD108*	Surface Mount Call Point
MBFD108*C	Surface Mount Call Point with Flap
MBFD900	Replacement glass (pkt of 10)
MBFD901	Clear polycarbonate flap
MBFD902	Test key

*Specify colour R = Red, W = White, Y = Yellow, B = Blue, G = Green

FD-109 Resettable Call Point



- One or two change over contacts
- Available in Red, Yellow or Green
- Resettable
- Supplied with transparent flap as standard
- With LED



Specifications:

Switch action:	One or two Single pole change over
Contact rating (A):	24VDC 3A
Monitoring resistor:	470Ω 1 W (others on request)
Protection:	IP42
Temp range (°C):	-10 to +55
Cable entry:	1 x 20mm through back box
Terminal Capacity:	3 x 1.5mm ² or 6 x 1.5mm ²
Construction:	High impact ABS
Dimensions (w x h x d):	92 x 92 x 56mm
Weight:	170g

Order Code	Description
MBFD109*LC1	Surface Mount Call Point one switch
MBFD109*LC2	Surface Mount Call Point two switch
MBFD908	Test Key

*Specify colour¹ R = Red, Y = Yellow, G = Green

¹ Other colours available subject to minimum order requirements