


MD6R21030A

NHP MOD6+ RCBO 6kA 1 Pole and Switched N 10A C Curve
30mA Type A



Component type	Earth leakage circuit breaker
Product status	New Item

ELECTRICAL

Rated current	10 A
Rated voltage	240 V
Rated leakage current	30 mA
Frequency	50 Hz
Rated short-circuit breaking capacity according to AS/NZS 61009	6 kA
Voltage type	AC
Trip curve	C
Rated impulse withstand voltage Uimp	4 kV
Leakage current type	A
Tripping time	300 ms
Min. service voltage	170 V
Max. operating voltage (Umax)	255 V
Rated residual make/break capacity	3000 A
Protected neutral pole	No
Number of poles (total)	2
Electrical life at Un, In (service cycles)	10000 cycles
Type of electric connection	Fork and pin
Isolator application	Yes
Rated insulation voltage Ui	500 V
Concurrently switching neutral conductor	Yes

CONSTRUCTION

Mounting method	DIN rail
Degree of protection (IP)	IP40
Number of protected poles	1

MECHANICAL

Mechanical life (service cycles)	20000 cycles
Connectable conductor cross section solid-core	1-35 mm ²

MD6R21030A

NHP MOD6+ RCBO 6kA 1 Pole and Switched N 10A C Curve
30mA Type A



MECHANICAL	Connectable conductor cross section multi-wired	1-35 mm ²
	Max. shock duration	13 ms
	Max. shock acceleration	25 g
DIMENSIONS	Depth	75 mm
	Height	85 mm
	Width	35 mm
	Weight	0.2 kg
	Width in number of modular spacings	2
ENVIRONMENT	Operating temperature	-25...55 °C
	Pollution degree	2