

Catalogue No: **3PS9WAS**

3PS125 WALL BOX 60DEG M50 x 1.5mm W/O CABLE GLAND

Plugs, Sockets and Switches > Industrial Plugs and Sockets > Isolating Plugs and Sockets > Proconnect Plugs and Sockets > 150A Disconnect Plugs and Sockets (3PS125 Series) > Accessories



Representative Photo Only
(actual product may vary based on configuration selections)

3Ps125 Wall Box 60Deg M50X1.5 Without Cable Gland

- Available in five sizes including 30A, 50A, 90A, 150A and 250A (Maximum current rating to IEC60309)
- 3, 4 and 5 pin configurations with optional pilot pins, silver alloy tipped for low voltage drop and high arc resistance
- AC23 rating for making and breaking high inductive loads
- Connect and disconnect under load, eliminates the need for switching
- Interlocked socket and appliance inlet with 24 insert settings (Factory Set) preventing mismatching for a safe and reliable connection
- High ingress protection and exceptional impact resistance, IP66 / IK 08
- Resistance to most industrial chemicals, detergents and exposure to UV light
- Range of angled wall boxes, incline sleeves and handles for all plug and socket combinations

SPECIFICATIONS

Product Series	3PS
Component Type Plugs And Sockets	Accessory
Standards Compliance	AS/NZS 3947.3 IEC 60309-1 IEC 60529 IEC 60947-3

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-