

## Switches

The ISO range of surface switches are available with or without a back box providing the user flexibility to mix and match units as required. All units have certified AC23 and M ratings and comply with protection rating IP 66 when used in conjunction with a back box.

Switches are available with and without a back box in Grey (G) and without the back box in Resistant Orange (RO) and Resistant White (RW) material.



**Surface switches (Including back box)**

Current and Voltage Rating		No. of Switching Poles	AC 23 Rating	M Rating	Colour	Cat. No.
10 A 250 V		2	10 A	M80	Grey	ISOSW110PG
					Grey (with 63mm base)	ISOSW110PGDB
10A 250 V		1 (2 way)	10A	M80	Grey	ISOSW1102PG
					Grey	ISOSW115PG
15 A 250 V		2	15 A	M80	Grey (with 63mm base)	ISOSW115PGDB
20 A 250 V		2	20 A	M150	Grey	ISOSW120PG
32 A 250 V		2	32 A	M180	Grey	ISOSW132PG
10 A 500 V		3	10 A	M100	Grey	ISOSW310PG
20 A 500 V		3	20 A	M100	Grey	ISOSW320PG
32 A 500 V		3	32 A	M100	Grey	ISOSW332PG
40 A 500 V		3	40 A	M100	Grey	ISOSW340PG
50 A 500 V		3	50 A	M200	Grey	ISOSW350PG
32 A 500 V		4	20 A	M100	Grey	ISOSW420PG*
40 A 500 V		4	32 A	M100	Grey	ISOSW432PG*

## SWITCH YOUR SOLAR WITH ISO!

When you've invested in a grid-connect solar system, why would you risk using anything but the best in switching? ISO solves that dilemma!

To complete your commercial or domestic solar solution, choose the ISO range of IP 66 rated plugs and sockets, designed and tested to suit Australian conditions!



Scan the QR code to download the NHP Solar Power Solutions Brochure

