

DTRTN32300AD

NHP DIN-T Residual Current Breaker RCBO 10kA 3 Pole and Switched Neutral 32A D Curve 300mA Type A



Component type	Earth leakage circuit breaker
Range	MOD6+ Residual Current Devices
Model	N/A
Product status	New Item

NHP MOD6+ residual current devices (RCDs) offer a 6kA rating with a proven history in domestic and commercial applications. The MOD6+ RCD range offers many solutions for both 1 phase in 10mA and 30mA sensitivities as well as 3 phase in 30mA sensitivities. The MOD6+ RCDs can be easily installed into NHP loadcenters, as well as MOD6+ RCBOs into MOD6+ distribution Panelboards.

ELECTRICAL

Rated current	32 A
Rated voltage	415 V
Rated leakage current	300 mA
Frequency	50/60 Hz
Rated short-circuit breaking capacity according to AS/NZS 61009	10 kA
Voltage type	AC
Trip curve	D
Rated impulse withstand voltage Uimp	4 kV
Leakage current type	A
Tripping time	300 ms
Min. service voltage	207 V
Max. operating voltage (Umax)	457 V
Rated residual make/break capacity	6000 A
Protected neutral pole	No
Number of poles (total)	4
Electrical life at Un, In (service cycles)	10000 cycles
Type of electric connection	Fork and pin
Isolator application	Yes
Rated insulation voltage Ui	500 V
Concurrently switching neutral conductor	Yes

CONSTRUCTION

Mounting method	DIN rail
Degree of protection (IP)	IP40
Number of protected poles	3
Mechanical life (service cycles)	20000 cycles
Disconnection characteristic	Undelayed

MECHANICAL

DTRTN32300AD

NHP DIN-T Residual Current Breaker RCBO 10kA 3 Pole and Switched Neutral 32A D Curve 300mA Type A



MECHANICAL	Connectable conductor cross section solid-core	1-25 mm ²
	Connectable conductor cross section multi-wired	1-16 mm ²
DIMENSIONS	Depth	77.1 mm
	Height	117.5 mm
	Width	72 mm
	Weight	0.64 kg
	Width in number of modular spacings	4
ENVIRONMENT	Operating temperature	-5...55 °C
	Pollution degree	2
	Ambient temperature during operating	-5...55 °C