

LazrSPEED® 550 SC to Unconnectorized, Fiber Pigtail, 0.9 mm Tight Buffer, 12-fiber Kit, Blue - Aqua (1-12)

Product Classification

| | |
|------------------------------|---|
| Portfolio | CommScope® |
| Brand | LazrSPEED® |
| Product Type | Fiber pigtail, multi-fiber |
| Regional Availability | Asia Australia/New Zealand EMEA Latin America North America |

Construction Materials

| | |
|-------------------------------|---------------------|
| Fiber Type | OM4, LazrSPEED® 550 |
| Total Fibers, quantity | 12 |

Dimensions

| | |
|-----------------------------|--|
| Cord Length, maximum | 23 ft 7 m |
| Cord Length, minimum | 2 ft 1 m |
| Ordering Note | For lengths greater than 999 ft (304 m), orders must be in meters Minimum length may vary based on cable configuration |

Environmental Specifications

| | |
|------------------------------|--------------------------------------|
| Environmental Space | Plenum |
| Operating Temperature | -10 °C to +60 °C (+14 °F to +140 °F) |

General Specifications

| | |
|-------------------------------|--------------|
| Construction Type | Pigtail kit |
| Interface, connector A | SC/UPC |
| Interface, connector B | Unterminated |
| Color, connector A | Beige |

Mechanical Specifications

| | |
|--|---------------------------------|
| Cable Retention Strength, maximum | 1.00 lb @ 0 ° 1.00 lb @ 90 ° |
|--|---------------------------------|

Regulatory Compliance/Certifications

| Agency | Classification |
|-----------------|--|
| RoHS 2011/65/EU | Compliant |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |



Included Products

X-TB-5K (Product Component—not orderable) — LazrSPEED® 900µm Tight Buffered Fiber

- CS-5K-TB (Product Component—not orderable) — LazrSPEED® 550 OM4 Bend-Insensitive Multimode Fiber

460125834 (Product Component—not orderable) — Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, multimode