


Accessories Type:OSLN

OSLN Type



Application : Lock Nut

- * Secure a cable gland in position of the equipment
- * Material : Brass, Nickel plated brass(Standard), Stainless steel

Order Example

Model	Thread size	Material
OSLN	M16	Nickel Plated Brass
OSLN	NPT 1/2"	Nickel Plated Brass
OSLN	PF 1-1/4"	Stainless Steel

● Metric & PG Type

(* in mm)

Metric Thread				OSPG-R Thread							
Part No.	H	P	L	Part No.	H	P	L	Part No.	H	P	L
OSLN - M16	22	25	4	OSLN - PG7	15	16.5	3	OSLN - PG M12	14	15	3
OSLN - M20	27	31	4	OSLN - PG9	18	20	3	OSLN - PG M16	18	20	3
OSLN - M25	32	36.5	4	OSLN - PG11	21	23.5	3	OSLN - PG M20	22	24.5	3
OSLN - M32	39	44.5	5	OSLN - PG13.5	23	25.5	3	OSLN - PG M25	27	29.5	4
OSLN - M40	48	55	5	OSLN - PG16	26	29	3	OSLN - PG M32	36	39.5	4
OSLN - M50	60	69	5	OSLN - PG21	32	35.5	4	OSLN - PG M40	45	50	5
OSLN - M63	73	84	6	OSLN - PG29	41	45	4	OSLN - PG M50	54	59	5
OSLN - M75	85	98	6	OSLN - PG36	51	56	5	OSLN - PG M63	67	73	6
OSLN - M90	102	117	10	OSLN - PG42	60	65	5	Note. For OSPG-R metric thread type.			
OSLN - M100	112	128	12	OSLN - PG48	66	73	6				

● NPT & PF Type

(* in mm)

Type	NPT Thread			Type	PF Thread		
Part No.	H	P	L	Part No.	H	P	L
OSLN - 1/2"	27	31	4	OSLN - 1/2"	27	31	4
OSLN - 3/4"	32	36	4	OSLN - 3/4"	32	36	4
OSLN - 1"	39	45	5	OSLN - 1"	39	45	5
OSLN - 1-1/4"	48	55.5	5	OSLN - 1-1/4"	48	55.5	5
OSLN - 1-1/2"	58	67	6	OSLN - 1-1/2"	58	67	6
OSLN - 2"	73	84	6	OSLN - 2"	73	84	6
OSLN - 2-1/2"	85	98	6	OSLN - 2-1/2"	85	99	6
OSLN - 3"	102	119	10	OSLN - 3"	102	119	10
OSLN - 3-1/2"	112	126	12	OSLN - 3-1/2"	112	128	12
OSLN - 4"	125	144	12	OSLN - 4"	125	144	12