

XLPE/PVC 4C+E

XLP 4X16E PC XLPPVC

Contact

OLEX CUSTOMER SERVICE - Purchase orders, invoices, general enquiries
Phone: 1300 CABLES
olex.customerservice@nexans.com

Nexans ref.: HTHP15AA004OMAA

GTIN: 9319215276457

4X16mm² + E XLPE/PVC Circular Orange

DESCRIPTION

- 4 core+earth, circular,
- 0.6/1kV X-90 insulated,
- PVC sheathed to AS/NZS 5000.1
- Copper conductors, 90°C.

Note: Earth cores smaller than 25mm² are not compacted.

Orange Circular; Circo



STANDARDS

National AS/NZS 1125; AS/NZS 5000.1



Rated Voltage U_o/U (Um)
0.6/1 kV



Cable flexibility
Rigid

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 9/03/21 www.olex.com.au Page 1 / 2

XLPE/PVC 4C+E

XLP 4X16E PC XLPPVC

Contact

OLEX CUSTOMER SERVICE - Purchase
orders, invoices, general enquiries
Phone: 1300 CABLES
olex.customerservice@nexans.com

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
With Green/Yellow core	Yes
Outer sheath	PVC
Colour	Orange
Type of conductor	Stranded copper
With smaller neutral conductor	No
Insulation	X-90

Dimensional characteristics

Nominal insulation thickness	0.8 mm
Number of earth cores	1
Nominal outer sheath thickness	1.8 mm
Number of cores	4
Earth conductor cross section	6 mm ²
Conductor cross-section	16 mm ²
Nominal overall diameter	20.4 mm
Approximate weight	89.0 kg/100m

Electrical characteristics

Inductive reactance at 50Hz	0.067 Ohm/km
Conductor AC resistance at 50 Hz	0.247 Ohm/km
Max. DC resistance of the conductor at 20°C	1.15 Ohm/km
Insulation resistance at 20°C	520.0 MOhm.km
Rated Voltage U ₀ /U (U _m)	0.6/1 kV

Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------