

PRODUCT DATASHEET

LED PERFORMANCE STICK 9 W/2700K E27 DIM

LED PERFORMANCE STICK | LED lamps, classic stick shape



- Areas of application
 - Suitable for indoor applications
 - Replacement for conventional compact fluorescent lamps with 15 W and 24 W

- Product benefits
 - Creation of the preferred light ambience thanks to dimming
 - Wide beam angle: 200°
 - Instant 100 % light, no warm-up time
 - Stylish and modern design
 - No UV and near-IR radiation in the light beam
 - Reliable operation thanks to brand quality
- Product features
 - Dimmable (with many common dimmers, see also www.ledvance.com/dim)
 - Long lifetime: up to 25,000 h
 - Mercury-free lamps
 - Input voltage: 220...240 V_{AC}
 - Storage temperature from -20 °C to up to +80 °C, up to 95 % relative humidity
 - Operating temperature from -20 °C to up to +35 °C, up to 95 % relative humidity



TECHNICAL DATA

Electrical data

Rated wattage	9.00 W
Nominal wattage	9.00 W
Nominal voltage	220...240 V
Operating frequency	50...60 Hz
Power factor λ	0.70
Claimed equiv. conventional lamp power	70 W

Photometrical data

Rated luminous flux	900 lm
Rated color temperature	2700 K
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	900 lm
Color rendering index Ra	80
Standard deviation of color matching	≤ 6 sdcn
Nominal luminous flux	900 lm
Color rendering index Ra	80

Light technical data

Warm-up time (60 %)	0.50 s
Starting time	0.5 s

Dimensions & weight



Overall length	114.0 mm
Diameter	41.0 mm
Outer bulb	-

Length	114.0 mm
---------------	----------

Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	E27
Mercury-free	Yes
Show WEEE picto	Yes
Product remark	All technical parameters apply to the entire lamp. Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value.
Mercury content	0.0 mg

Capabilities

Dimmable	Yes
-----------------	-----

Certificates & standards

Energy efficiency class	A+
Energy consumption	9 kWh/1000h

Country-specific categorizations

Order reference	LP STICKDIM9W/8
------------------------	-----------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075129269	Folding carton box 1	42 mm x 42 mm x 117 mm	88.00 g	0.21 dm ³
4058075129276	Shipping carton box 10	218 mm x 92 mm x 132 mm	951.00 g	2.65 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.