

SPECIFICATION SHEET

Product
Code

Mini Globes - MGC

Description

Mini Globe – Clear (Dimmable)





Specification features

- Long lifetime 15000hrs
- UV and IR radiation can be avoided
- Low temperature while high power operation
- Easy for installation
- Mercury-Free
- Delivering nearly the same light output as incandescent bulb

Application

- Operating temperature range is between -20°C ~ $+45^{\circ}\text{C}$
- Only for indoor application

PRODUCT TESTING	CERTIFICATION	DISTRIBUTION	DIMENSIONS(mm)
			



Product Code	Voltage [1] / Current (ma)	Watt./PF (min)	Ra	Luminous Flus	Beam Angle	Lifetime	Dim	Temp Colour	Cap
MGC5.5WLEDE14WW-D	220-240v/45	5.5W/0.7	≥80	350LM	200°	15,000h	YES	2700K	E14
MGC5.5WLEDE27WW-D	220-240v/45	5.5W/0.7	≥80	350LM	200°	15,000h	YES	2700K	E27
MGC5.5WLEDB15WW-D	220-240v/45	5.5W/0.7	≥80	350LM	200°	15,000h	YES	2700K	B15
MGC5.5WLEDB22WW-D	220-240v/45	5.5W/0.7	≥80	350LM	200°	15,000h	YES	2700K	B22
MGC5.5WLEDE14CW-D	220-240v/45	5.5W/0.7	≥80	350LM	200°	15,000h	YES	4000K	E14
MGC5.5WLEDE27CW-D	220-240v/45	5.5W/0.7	≥80	350LM	200°	15,000h	YES	4000K	E27
MGC5.5WLEDB15CW-D	220-240v/45	5.5W/0.7	≥80	350LM	200°	15,000h	YES	4000K	B15
MGC5.5WLEDB22CW-D	220-240v/45	5.5W/0.7	≥80	350LM	200°	15,000h	YES	4000K	B22