



P D L

NEW PRODUCT DATA AND APPLICATION SHEET

CATALOGUE #

WSW321 SURF SW 1G 32A L/GY

BARCODE #

9416175228650

DESCRIPTION

IP56 Weather Protected 32A Isolating Switch



WSW321



WSW321 – Side

BOX QUANTITY 1

OUTER QUANTITY 6

FEATURES

Standard depth base
Aesthetically superior design
Available in Light Grey
32A Switch as standard
Protection rating IP56
Latest technology materials with superior UV protection, impact strength, and additional chemical resistance when compared with polycarbonates
Supplied complete with base and accessory pack for ease of installation
Channelled red gaskets
Pad lockable for Isolation
Clearly marked terminals
Captivated stainless steel fixing screws, only two screws needed.
Base includes 90° mounting options – added flexibility
Five plain 25mm conduit side entry points
Single rear 25mm conduit entry point
Plain and threaded 25-20mm reducers supplied as appropriate



P D L

NEW PRODUCT DATA AND APPLICATION SHEET

SPECIFICATIONS 250Vac, 50Hz, Single Pole, 1 Way.
32A
20AX fluorescent
M180 Motor Rating
Terminals accommodate 2x6mm² each
AC21A -32A & **AC23A** -3Kw-21A Utilisation Categories
IP56 Environmental Protection Rating
DIMENSIONS:
Standard Dimensions: 84mm x 84mm x 72mm

APPLICATIONS This IP56 Isolator switch can be used for a vast array of applications including, air-conditioning, fixed plant, commercial & outdoor lighting, plus many others.