

PMA Connectors Metric, Metal Thread

VN /straight, metric, metal

These PMAFIX connectors are generally used in the heavy machine and railway vehicle construction sectors, where increased demands are made of the system properties. Together with PMAFLEX conduits, these products offer the highest grade of safety and sealing.



- High-grade formulated polyamide
- Thread made of nickel-plated brass
- Self-extinguishing, free from halogens and cadmium
- Excellent impact strength
- Extremely high thread and system connection strength
- Temperature range: – 40 °C to 105 °C; Short-term to 160 °C
- Content of delivery: Fitting with oval clips (OVN2), conduit and thread seal (NVN3, SVN4 or OR)

Order No. IP68 Black	Thread metric	Fits to conduit size		Thread Length (g)	Overall Length (A)
		NW	metric		
NVNV-M120-10	M12x1.5	10	12	10.0 mm	40.0 mm
NVNV-M120-5	M12x1.5	10	12	5.0 mm	35.0 mm
NVNV-M160-10	M16x1.5	10	12	10.0 mm	40.0 mm
NVNV-M160-5	M16x1.5	10	12	5.0 mm	35.0 mm
NVNV-M162-10	M16x1.5	12	16	10.0 mm	43.0 mm
NVNV-M162-5	M16x1.5	12	16	5.0 mm	38.0 mm
NVNV-M202-10	M20x1.5	12	16	10.0 mm	43.0 mm
NVNV-M202-6	M20x1.5	12	16	6.0 mm	39.0 mm
NVNV-M207-10	M20x1.5	17	20	10.0 mm	51.0 mm
NVNV-M207-6	M20x1.5	17	20	6.0 mm	47.0 mm
NVNV-M257-11	M25x1.5	17	20	11.0 mm	52.0 mm
NVNV-M257-7	M25x1.5	17	20	7.0 mm	43.0 mm
NVNV-M253-11	M25x1.5	23	25	11.0 mm	54.0 mm
NVNV-M253-7	M25x1.5	23	25	7.0 mm	50.0 mm
NVNV-M323-13	M32x1.5	23	25	13.0 mm	56.0 mm
NVNV-M323-8	M32x1.5	23	25	8.0 mm	51.0 mm
NVNV-M329-13	M32x1.5	29	32	13.0 mm	57.3 mm
NVNV-M329-8	M32x1.5	29	32	8.0 mm	52.3 mm
NVNV-M409-13	M40x1.5	29	32	13.0 mm	57.3 mm
NVNV-M409-8	M40x1.5	29	32	8.0 mm	52.3 mm
NVNV-M406-13	M40x1.5	36	40	13.0 mm	71.4 mm
NVNV-M406-8	M40x1.5	36	40	8.0 mm	66.4 mm
NVNV-M506-14	M50x1.5	36	40	14.0 mm	72.4 mm
NVNV-M506-9	M50x1.5	36	40	9.0 mm	67.4 mm
NVNV-M508-14	M50x1.5	48	50	14.0 mm	72.4 mm
NVNV-M508-9	M50x1.5	48	50	9.0 mm	67.4 mm
NVNV-M638-14	M63x1.5	48	50	14.0 mm	72.4 mm
NVNV-M638-10	M63x1.5	48	50	10.0 mm	68.4 mm

