

CS/CU-Z25XKR-1

CS-Z25XKRW-1
Cooling Capacity (kW)
2.50 (0.95-3.70)
Heating Capacity (kW)
3.20 (0.90-4.40)
Air Flow (L/s)
188/200
Dehumid (L/h)
1.50
Running Current (A)
2.50/3.20
Power Input (kW)
0.57 (0.22-1.2)/0.73 (0.19-1.29)
AEER/EER (W/W)
4.32/4.39
ACOP/COP (W/W)
4.33/4.38

21/02/2023, 11:56

Star Rating

4.0/6.5

Inside Sound Pressure Level (dB) (Hi/Lo/S-Lo)

40/25/19

Outside Sound Pressure Level (dB) (Hi/S-Lo)

49/44

Sound Power Level (db) (Hi/S-Lo)

64/59

Net Weight - Indoor (Outdoor)

8 (25)

Dimensions – Indoor (Outdoor) (h x w x d)

290 x 779 x 209

Refrigerant Pipe Diameter - Liquid Side (mm/(in))

6.35 (1/4)

Refrigerant Pipe Diameter - Gas Side (mm/(in))

9.52 (3/8)

Pipe Extension Length Min-Max (m)

3~20

Pipe Length for Additional Gas (m)

7.5

Additional Gas Amount (g/m)

10

Power Supply

Outdoor

21/02/2023, 11:56

Operating Range (Outdoor) – Cooling (C)

-10 ~ +46

Operating Range (Outdoor) – Heating (C)

-15 ~ +24

Refrigerant Type

R32

Air > Panasonic Air Solutions > Conditioning Home Air > Conditioners Single Room Air Conditioners

Air > Reverse Cycle > CS/CU-Wall > Z25XKR-1 > All Specs