



Starburst Crystal ECO LED GEN II Downlight

Pierlite multi-function fixed or gimble 60 degree beam reflector style downlight. A low maintenance solution that is ideal for residential apartments, foyers, retail, restaurants and clubs where an energy efficient and reliable lamp performance is essential.

- One box solution with 2-in-1 cut-out sizes and fixed or gimble formats
- Cut-out 90mm, adjustable to 70mm by removing posts on trim
- Install as a fixed downlight by using the locking ring in the box
- Integrated dimmable driver
- Superior glare control with multi-faceted optics
- Easy to install with flexible clips and pre-wired with 1.2m flex and plug
- Available in 3000K (warm white) and 4000K (natural white)
- 3 year warranty



3
 YEAR
 WARRANTY*


IP20
 RATED


DIMMABLE


GENERAL SPECIFICATION

Item Code	Description		Wattage	Lumen Output	Colour Temperature	CRI	Dimmable
CRYSECO5G2	CRYSTAL ECO 4000K WH IN-BUILT DRIVER D/LIGHT		9W	880Lm	4000K	80	Yes
Dimming Technology	IP Rating	Finish	Colour	Weight	Beam Angle	Beam Distribution	Voltage
Phase	IP20	Powdercoated	White	0.7kg	60°	Symmetric	240V
Dimensions H x W x L (mm)	Tilt	Circuit Wattage	Chip Configuration	Heat Sink Material	Lamp Type	Operating Temperature	
81	30°	11.5W	COB	Aluminium (Die Cast)	LED (COB)	0 to 40°C	

Starburst Crystal ECO LED GEN II Downlight

PRODUCT IMAGES



LINE DRAWINGS

