

MaxiMaster Floodlight Gen3

The MaxiMaster Floodlight has always had a trusted history of reliability through all variations of installations, the Gen3 is no exception and builds on the adaptability and versatility of its predecessor, the third generation provides the same shape and form as the generation 2 but with the added features of cable entries, terminal block, additional surge protection, lumen and colour select. Gen3 was built for the harsh Australian conditions for installations such as general industrial and public areas including warehousing, regional areas, transport facilities, custodial, schools, and heavy industry. The lumen and colour select technology provides the ability to have 1 luminaire with multiple wattages/lumen outputs in the same housing making it easier to replace keeping the same appearance through your installation.



LUMEN SELECT[®] | COLOUR SELECT


- Provided with multiple wattages/lumen outputs in 1 fitting with wattages of 100W/150W/200W/250W and colour select with 3000K/4000K/5000K
- Supplied with 2 x 20mm cable entries, 2 x 20mm metal cable gland, 6mm² terminal block and an additional 10KV surge protection installed to the 4KV driver surge immunity
- L80/B10 = 54,000 hours @ an ambient temp of 50°C

						
80	IP66	IK08	0 to 50	Non - Dimmable	54,000hrs (L70/B50) @ 50°C	5 Years
CRI	Ingress Protection Rating	Impact Rating	Operating Temperature	Dimming	Lifetime	Warranty

CODE	SYSTEM POWER	EXIT LUMEN	EFFICACY	CCT	DIMENSIONS
MML250LSCSA	250W	35500lm	150lm/W	4000K	L523 x W342 x H185 mm
	250W	32900lm	132lm/W	3000K	
	200W	26700lm	139lm/W		
	150W	21500lm	145lm/W		
	100W	14900lm	152lm/W		
	200W	28600lm	155lm/W		
	150W	22500lm	158lm/W		
	100W	15400lm	161lm/W		
	250W	34000lm	137lm/W	5000K	
	200W	27900lm	145lm/W		
	150W	22200lm	151lm/W		
	100W	15300lm	161lm/W		
MML250LSCSS	250W	36200lm	158lm/W	4000K	L523 x W342 x H185 mm
	250W	33600lm	139lm/W	3000K	
	200W	27500lm	146lm/W		
	150W	21800lm	152lm/W		
	100W	15000lm	159lm/W		
	200W	29300lm	162lm/W		
	150W	23100lm	152lm/W		
	100W	15500lm	169lm/W		

MML250LSCSS	250W	34800lm	145lm/W	5000K
	200W	28500lm	153lm/W	
	150W	22800lm	159lm/W	
	100W	15600lm	165lm/W	

Line Drawings



Product Images



MML250LSCSA



MML250LSCSA



MML250LSCSA



MML250LSCSS



MML250LSCSS



MML250LSCSS

