
# **Mine Master LED**

Purpose designed IP66 fixture with LED technology for the mining industry.



## **Specification**

·Average rated LED lamp life of 50,000 hours at L70 in Ta40C environments ·Durable aluminium or stainless steel body options ·High performance optics with improved illumination uniformity ·UV resistant moulded lens with integral IP66 silicone seal ·Pre-wired maintained with remote emergency box option available ·Suits standard diameter 34mm poles and spigot brackets ·Amber and green LED emergency versions available on request





#### **Quick Spec**

Pierlite Mine Master LED, IP66, dia. 34mm spigot mount fixture with integral driver and micro optical system. Supplied with power supply cable, internal circuit protection. Select LM6 aluminium body (MRA) or 316 Stainless steel body (MRS) version.

### **Design Application**

Designed for the safe illumination of infrastructure such as conveyors, walkways and platforms on mines, power stations, wharves, sugar mills, eye wash stations and general industrial plants.

#### **Product Codes**

Code	Version	Dim (mm)	Mass (kg)
MRA52L2	52W Alum. LED Asymm	204 x 380	3.2
MRS52L2	52W SS LED Asymm.	204 x 380	4.5
MRA32L2	32W LED 6K Alum.	204 x 380	4.3
MRA46L2X1	46W AI. LED Amber. MRA46L2X1 Assy.	204 x 380	4.7
MRS46L2X1	46W SS LED AMBER Asym.	204 x 380	3.2
MRS32L2	32W SS LED 6K Asym.	204 x 380	4.5

