



Quick Overview

36kV Indoor - Single Core XLPE

Features

Raychem IXSU - Indoor MV Termination for Polymeric Cables

- No sheds for indoor applications up to 42 kV
- High-performance termination material
- New ceramic stress control system
- Simple to install, high reliability
- No shelf life limitation
- Non conductive trifurcation
- Conductor Size 120-400 mm²

Details

Part No. RAYIXSU-F6141

Brand Raychem

Unit Of Measure Set

Compendium Page # 382

Additional Information

SINGLE CORE		THREE CORE		UOM	Pack Qty	Ctn Qty
Part No.	Conductor Size (mm ²)	Part No.	Conductor Size (mm ²)			
12kV	12kV Indoor - Single Core XLPE	24kV	24kV Indoor - 3 Core XLPE - 450 Tail Length			
	RAYIXSU-F3111 10-35		RAYIXSU-F5311-NC 10-25	Kit	1	1
	RAYIXSU-F3121 25-95		RAYIXSU-F5321-NC 25-50	Kit	1	1
	RAYIXSU-F3131 95-240		RAYIXSU-F5331-NC 70-185	Kit	1	1
	RAYIXSU-F3141 240-500		RAYIXSU-F5341-NC 185-400	Kit	1	1
	RAYIXSU-F3151 500-800			Kit	1	1
RAYIXSU-F3161 1000-1200		Kit	1	1		
12kV	12kV Indoor - 3 Core XLPE - 450 Tail Length	36kV	36kV Indoor - Single Core XLPE			
	RAYIXSU-F3311-NC 16-35		RAYIXSU-F6131 50-120	Kit	1	1
	RAYIXSU-F3321-NC 25-70		RAYIXSU-F6141 120-400	Kit	1	1
	RAYIXSU-F3331-NC 95-240		RAYIXSU-F6151 400-800	Kit	1	1
RAYIXSU-F3341-NC 240-500		Kit	1	1		
24kV	24kV Indoor - Single Core XLPE	36kV	36kV Indoor - 3 Core XLPE - 650 Tail Length			
	RAYIXSU-F5121 25-70		RAYIXSU-F6332-NC 50-120	Kit	1	1
	RAYIXSU-F5131 70-240		RAYIXSU-F6342-NC 120-300	Kit	1	1
	RAYIXSU-F5141 185-400		RAYIXSU-F6352-NC 400-500	Kit	1	1
RAYIXSU-F5151 400-800		Kit	1	1		

Proudly Distributed By



☎ 1300 555 586

🌐 www.repelec.com.au

✍ Sign up or log in to repelec.com.au

📘 📷 🐦 📺 @RepelecAU

Page 2