

Rittal – The System.

Faster – better – everywhere.

Mounting angles, 482.6 mm (19") for TS – DK 7827.201

Date : Aug 3, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Mounting angles, 482.6 mm (19") for TS – DK 7827.201

created: 03.08.2016 build on www.rittal.com/au-en



Product description

Benefits: Integral U markings in the front facilitate systematic assembly within the 482.6 mm (19") attachment level.
L-shaped mounting angles accommodate the installation kits of server systems on Suitable for 482.6 mm (19") partial installation

Material: Sheet steel, 2 mm

Technical specifications: Integral 482.6 mm (19") punchings (EIA standard)
Side round and square punchings
Clear chromated for conductive connection of the 482.6 mm (19") installed equipment.

Supply includes: Assembly parts

Packs of: 2 pc(s).

EAN: 4028177234949

Customs tariff number: 73269098



eCl@ss 5.1: 27182504

eCl@ss 7.0: 27189261

ETIM 6.0: EC002620

Product features

Design: L-shaped mounting angle

To fit:	Enclosure type: TS Height: = 2000 mm
Dimensions:	Width: 19"
Units:	42 U
Weight/pack:	4.84 kg
Downloads	
Data sheets:	 Technical details EN
Documentation:	 Instructions (DE, ES, DA, EN, FR, NL, IT)
CAD drawings:	Request