

COMMERCIAL LED CORROSION PROOF FITTINGS


NEW!



VULCAN LED Corrosion Proof Available in 1,200mm (4ft) Single & Double, Standard or Emergency

- LED replacement for 36W fluorescent fittings
- >100 lumens per circuit watt
- 5,000K cool white light output
- 50,000 hour average rated LED life
- IP65, can be used for internal or external applications
- Complete with stainless steel clips
- Plastic clips available (RCPPCCLIPS)
- Tamper proof screws can be used to aid security of the fitting
- Emergency versions c/w test switch provides 2 hour emergency duration
- 10% lumen output in emergency mode
- High impact rating IK08

	1 x 24W	2 x 24W
Standard	R124LEDCP-01	R224LEDCP-01
Emergency	R124LEDCPE-01	R224LEDCPE-01
Comparable to:	1 x 36W T8 fluorescent	2 x 36W T8 fluorescent
Total Power (W):	24	48
Power Factor:	>0.9	>0.9
Total Light Output (lm):	2,700	4,800
Beam Angle (deg):	110	110
Lux at 1m (lux):	685	1,350
CCT (K):	5,000	5,000
CRI:	80	80
Efficacy (lm/cctW):	>100	>100
Lifetime (hrs):	50,000	50,000
Length (mm):	1,258	1,258
Width (mm):	93	140
Height (mm):	97	97
Weight (kg):	2.5	3.0
IP:	65	65



	LENGTH	WIDTH	HEIGHT
R124LEDCP-01	1258mm	93mm	97mm
R124LEDCPE-01	1258mm	93mm	97mm
R224LEDCP-01	1258mm	140mm	97mm
R224LEDCPE-01	1258mm	140mm	97mm


COMMERCIAL
LED CORROSION PROOF FITTINGS

VULCAN LED Corrosion Proof
Available in 600mm (2ft) Single & Double

- LED replacement for 18W fluorescent fittings
- >100 lumens per circuit watt
- 5,000K cool white light output
- 50,000 hour average rated LED life
- IP65, can be used for internal or external applications
- Complete with stainless steel clips
- Plastic clips available (RCPPCCLIPS)
- Tamper proof screws can be used to aid security of the fitting
- High impact rating IK08
- Emergency version c/w test switch provides 2 hour emergency duration
- 10% lumen output in emergency mode



	1 x 12W	2 x 12W
Standard	R112LEDCP-01	R212LEDCP-01
Emergency		R212LEDCPE-01
Comparable to:	1 x 18W T8 fluorescent	2 x 18W T8 fluorescent
Total Power (W):	12	24
Power Factor:	>0.9	>0.9
Total Light Output (lm):	1,300	2,650
Beam Angle (deg):	110	110
Lux at 1m (lux):	360	720
CCT (K):	5,000	5,000
CRI:	80	80
Efficacy (lm/cctW):	>100	>100
Lifetime (hrs):	50,000	50,000
Length (mm):	660	660
Width (mm):	93	140
Height (mm):	97	97
Weight (kg):	1.1	1.35
IP:	65	65



	LENGTH	WIDTH	HEIGHT
R112LEDCP-01	660mm	93mm	97mm
R212LEDCP-01	660mm	140mm	97mm
R212LEDCPE-01	660mm	140mm	97mm



COMMERCIAL

LED CORROSION PROOF FITTINGS

Designed for demanding industrial applications, the ROBUS VULCAN is the ultimate energy saving, corrosion-proof LED solution for car parks, cold stores, corridors and garages. The range provides an equally wide illumination pattern to replace waterproof linear fluorescent.

FEATURES:

CORROSION PROOF

IP65

HIGH STRENGTH POLYCARBONATE BASE & DIFFUSER

Wide beam angle and no glare
Evenly diffused light

EASY INSTALLATION

Supplied with LED Driver
Plug & Play mains connection system
Tool-free removable gear tray
Stainless steel diffuser clips
Surface or Chain Suspension

COST EFFECTIVE

35% energy saving
50,000 hour LED lamp life
Reduced energy, maintenance and disposal

WIDE RANGE OF APPLICATIONS

No heat filaments or electrodes
Resistant to shock and vibration

PERFORMANCE DRIVEN

100 lumens per circuit watt
SMD LED's
5 year warranty



COMMERCIAL
LED CORROSION PROOF FITTINGS

THE DIRECT LINEAR FLUORESCENT REPLACEMENT

Single 4FT	R124LEDCP-01
Double 4FT	R224LEDCP-01
Single 2FT	R112LEDCP-01
Double 2FT	R212LEDCP-01

VULCAN
BUILT TO LAST



4FT Single



4FT Double



2FT Single



2FT Double