

COMMERCIAL SPACE LED PANEL



SPACE LED panel, 600x600mm, white

- Suitable for use in offices, shops, hotels, restaurants, reception areas, schools, health centres, hospitals
- LED replacement for 4 x 18W T8
- Fits into standard sizes of ceiling grid – 15mm and 24mm
- 50,000 hour average lamp life. Up to 5 times that of a standard fluorescent
- 4 wire suspension system available – can suspend panel to a length of 1.2M (RAMSUS-4W)
- Surface mounted boxes available (R6060SMKFB-01 and R6060SMKFBS-01)
- Simple to install and low/no maintenance
- C/w 1m flex and plug
- High efficacy of 94-111lm/W
- Suitable for switching by external PIR, Microwave or Photocell



APC Group, Bassenden, Western Australia

30W

	Neutral White RP30406060-01	Daylight White RP30656060-01
Comparable to:	4X18W	4X18W
Total Power (W):	28.7	28.5
Power Factor (PF):	0.95	0.95
Total Light Output (lm):	3,180	3,060
Efficacy (lm / cctW):	111	107
Lifetime (hrs):	50,000	50,000
Lux at 1m (lx):	1,090	1,060
Beam Angle (deg):	110	110
CCT (K):	4000	6500
CRI:	80	80
IP:	20	20
Length (mm):	595	595
Width (mm):	595	595
Depth (mm):	9	9
Weight (kg):	3	3

40W

	Neutral White RP40406060-01	Daylight White RP60656060-01
Comparable to:	4X18W	4X18W
Total Power (W):	37.7	37.1
Power Factor (PF):	0.95	0.95
Total Light Output (lm):	3,650	3,470
Efficacy (lm / cctW):	97	94
Lifetime (hrs):	50,000	50,000
Lux at 1m (lx):	1,260	1,190
Beam Angle (deg):	110	110
CCT (K):	4000	6500
CRI:	80	80
IP:	20	20
Length (mm):	595	595
Width (mm):	595	595
Depth (mm):	9	9
Weight (kg):	3	3

