

COMMERCIAL SULTAN LED CORROSION PROOF CCT3

Sleek, slim and robust, the new SULTAN LED Corrosion Proof CCT Selectable from ROBUS is a perfect LED retrofit solution where fluorescent corrosion proofs are used. The high strength polycarbonate housing and evenly diffused light is perfect for use in car parks, cold stores, corridors and garages. Colour temperature can be selected on site which has benefits to the wholesaler, installer and end user.

INTEGRAL MICROWAVE SENSOR VERSIONS HAVE THE ROBUS 3-STEP DIMMING FUNCTION;

- Full brightness on detection of movement
- Selectable background light after no-detection hold time
- Off after a further standby time (this time can be ∞)
- Selectable detection zone sensitivity, Lux switching point, background light levels, hold and standby times
- Cost effective functional solution for energy saving when the area is vacated

Available in:

Single 2FT, CCT Selectable	RSU1206CCT3-24
Single 4FT, CCT Selectable	RSU2412CCT3-24
Double 2FT, CCT Selectable	RSU2406CCT3-24
Double 2FT, CCT Selectable, Emergency	RSU2406CCT3E-24
Double 4FT, CCT Selectable	RSU4812CCT3-24
Double 4FT, CCT Selectable, Emergency	RSU4812CCT3E-24
Double 4FT, CCT Selectable, Dual Wattage	RSU4812CCT3DP-24
Double 2ft, CCT Selectable, Dual Wattage & Emergency	RSU4812CCT3DPE-24
Double 4ft, CCT Selectable, Standard 110-240V	RSU4812CCT3110-24
Double 4ft, CCT Selectable, Emergency 110-240V	RSU4812CCT3110E-24

FEATURES:

CCT3 SELECTABLE

Colour Temperature Selectable between 3000, 4000 and 6500K

AVAILABLE WITH MW SENSOR WITH 3-STEP DIMMING FUNCTION

Cost effective and energy saving

CORROSION PROOF

IP65

SLIM PROFILE

85mm wide for single fittings
103mm wide for double fittings

HIGH STRENGTH POLYCARBONATE

BASE & DIFFUSER

Wide beam angle and no glare
Evenly diffused light

EASY INSTALLATION

Wire through the back or from either end

COST EFFECTIVE

50,000 hour rated LED life
Reduced energy, maintenance and disposal costs

WIDE RANGE OF APPLICATIONS

No heat filaments or electrodes
Resistant to shock and vibration
Withstands temperatures of -25°C

PERFORMANCE DRIVEN

Up to 114 lumens per circuit watt
5 year warranty