



CLARE S9062TC/S - 10W

Recessed LED downlight with sensor control and selectable colour temperature.

Application

Ideal for interior service areas, bathrooms and storage spaces

Design Specifications

- Selectable colour temperature with an integral DIP switch 3000K / 4000K / 5700K
- Integral PIR sensor control with a fixed 60 seconds ON motion detection function incorporating a light sensor function to engage when the lighting levels are <20lux
- Integral non-dimmable LED 10 watt control gear, IC - 4 rated.
- Designed with flex and plug for easy installation
- Stylish white trim and opal polycarbonate diffuser
- Cut - out 92mm



Performance

In Built Sensor - **YES**

Sensor Type - **PIR**

Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)	CRI
S9062TC/S	240	10	760/800/850	3000/4000/5700	90	80

Model No.	Body Colour	Cut Out (mm)	Dim (mm)
S9062TC/S	WHITE	92	115(W) x 73(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".


Dimensions

Model No.	Input (V/AC)	Power (W)	Lumens (lm)	Size Current (A)	In-rush Current (A)	CB	CCT (K)	Beam Angle (°)	Max. Dia (mm)	Dimension (mm)
S9062TC/S	240/250	10	760/800/850	0.04	0.15	10/15	3000/4000/5700	90	92	115(W) x 73(H)

Power (W)	Input (V/AC)	Beam Angle (°)	Beam Diameter (mm)	Beam Spread (mm)	Working Temperature (°C)	Time to Start (s)	Light Output (lm)	Installation Height (m)	Sensor Type
10	240/250	90	115	115	25	10	760/800/850	2.5	PIR

* It will turn off in 30 seconds if there is no motion detected.


S9062TC-S CUT - OUT 92mm



Photometric Data

Unit: cd C0/C180 — C90/C270 —

S9062TC/S at 3000K



THE SFI SYSTEM ELIMINATES LED FLICKERING.

**SIMPLY
MATCH THE
ECOGEN SFI
DOWNLIGHT
WITH THIS
SDD400SFI
DIMMER.**



**DIM with
FLICKER
CONTROL**

For related
products
please
scan me

