



LED TUBE LT8G - 9/18W

LED tube, G13 base

Application

Energy efficient LED lamp solutions

Design Specifications

- Fit new T8 LED fixture or retrofit T8 fluorescent fixture (Magnetic Ballast)
- Traditional full glass body construction, G13 lamp base
- High efficiency SMD LED chips, beam 320 degree
- Integral non-dimmable LED driver, 9 or 18 watt models
- Colour temperature 3000K, 4000K, 6000K, CRI >80
- No flicker, instant start, Safety LED fuse included, TYPE A classified product



Technical Specification

Model No.	Description	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
LT8G/60WW	T8 LED 600mm WARM WHITE W/FUSE	240	9	900	3000	80
LT8G/60CW	T8 LED 600 mm COOLWHITE W/FUSE	240	9	950	4000	80
LT8G/60DL	T8 LED 600 mm DAYLIGHT W/FUSE	240	9	1000	6000	80
LT8G/120WW	T8 LED 1200mm WARM W/FUSE	240	18	1800	3000	80
LT8G/120CW	T8 LED 1200mm COOL WHITE W/FUSE	240	18	1850	4000	80
LT8G/120DL	T8 LED 1200mm DAY LIGHT W/FUSE	240	18	2000	6000	80

Model No.	Base Type	Beam Angle (°)
LT8G/60WW	G13	320
LT8G/60CW	G13	320
LT8G/60DL	G13	320
LT8G/120WW	G13	320
LT8G/120CW	G13	320
LT8G/120DL	G13	320

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish.

Warning: The luminaire that these LED tubes are installed in may need to be converted in accordance with AS/NZS60598.2.1:2014 by a suitably qualified person. In all instances any electronic components (i.e. driver, electronic ballast, capacitor) must be removed from the circuit. Refer installation instructions for more details, in particular the orientation of the lamp ACTIVE supply.

Dimensions

LT8G60 - 26 x 600mm, LT8G120 - 26 X1200mm

