

Head Office

40 Biloela Street Villawood NSW 2163 T +612 9723 3099

46-48 Keys Road Moorabbin VIC 3189

F +613 9532 1838

Queensland 13/258 Musgrave Road Coopers Plains QLD 4108 T +617 3276 8897 F +617 3277 8817

WA Agencies Delta Lighting System 15 Hunt St. Malaga WA 6090 T +618 9249 4447 F +618 9249 2776



SL7269 & SL7270

BUTTON IP65 LED BUNKER LIGHT










DIMENSIONS



FEATURES

- · Die-cast aluminium body and ring
- Powder coated finish
- Opal polycarbonate diffuser
- High efficiency SMD LED chips
- Built-in LED driver
- IP65 weatherproof
 COLOUR TEMPERATURE
 5000K DAYLIGHT
 FITTING COLOUR
- White or Black

TECHNICAL SPECIFICATIONS

Model No.	Input Voltage	Power	Luminous Flux	Colour Temp	CRI (Ra)	Dimmable	Dimensions Ø x H	Fitting Colour
SL7269DL WH	240V~50Hz	6W	450lm	5000K	>80	No	165 x 65 mm	White
SL7269DL BK	240V~50Hz	6W	450lm	5000K	>80	No	165 x 65 mm	Black

Model I	Input Io. Voltage	Power	Luminous Flux	Colour Temp	CRI (Ra)	Dimmable	Dimensions Ø x H	Fitting Colour
SL7270DL	NH 240V~50Hz	12W	800lm	5000K	>80	No	210 x 85 mm	White
SL7270DL	3K 240V~50Hz	12W	800lm	5000K	>80	No	210 x 85 mm	Black