

Head Office

40 Biloela Street Villawood NSW 2163 F +612 9724 1899

46-48 Keys Road Moorabbin VIC 3189 T +613 9532 3168 F +613 9532 1838

Queensland

13/258 Musgrave Road Coopers Plains QLD 4108 T +617 3276 8897 F +617 3277 8817

WA Agencies

Delta Lighting System 15 Hunt St. Malaga WA 6090 T +618 9249 4447 F +618 9249 2776



SL9706 SLIMLINE











TECHNICAL SPECIFICATIONS

Model No.	Input Voltage	Power	Luminous Flux	Colour Temp	CRI (Ra)	Dimensions L x W x H	Fitting Colour
SL9706/280WW/FP	240V~50Hz	4W	300lm	3000K	>80	280 x 23 x 36 mm	White
SL9706/280DL/FP	240V~50Hz	4W	300lm	5000K	>80	280 x 23 x 36 mm	White
SL9706/280WW/HW	240V~50Hz	4W	300lm	3000K	>80	280 x 23 x 36 mm	White
SL9706/280DL/HW	240V~50Hz	4W	300lm	5000K	>80	280 x 23 x 36 mm	White
SL9706/540WW/FP	240V~50Hz	9W	750lm	3000K	>80	540 x 23 x 36 mm	White
SL9706/540DL/FP	240V~50Hz	9W	750lm	5000K	>80	540 x 23 x 36 mm	White
SL9706/540WW/HW	240V~50Hz	9W	750lm	3000K	>80	540 x 23 x 36 mm	White
SL9706/540DL/HW	240V~50Hz	9W	750lm	5000K	>80	540 x 23 x 36 mm	White
SL9706/840WW/FP	240V~50Hz	13W	1050lm	3000K	>80	840 x 23 x 36 mm	White
SL9706/840DL/FP	240V~50Hz	13W	1050lm	5000K	>80	840 x 23 x 36 mm	White
SL9706/1140WW/FP	240V~50Hz	18W	1550lm	3000K	>80	1140 x 23 x 36 mm	White
SL9706/1140DL/FP	240V~50Hz	18W	1550lm	5000K	>80	1140 x 23 x 36 mm	White
SL9706/1440WW/FP	240V~50Hz	22W	1800lm	3000K	>80	1440 x 23 x 36 mm	White
SL9706/1440DL/FP	240V~50Hz	22W	1800lm	5000K	>80	1440 x 23 x 36 mm	White


FEATURES

- Double insulated PVC housing
- Opal polycarbonate diffuser
- High efficiency SMD LED chip
- Seamless light output
- Built-in LED driver
- 1.2 m flex & plug fitted (For FP only)
 Mounting bracket and connector
- COLOUR TEMPERATURE 3000K WARM WHITE 5000K DAYLIGHT
- FITTING COLOUR White - Powder coated finish

ACCESSORIES

- SL9706/32CM LINK
- SL9706/76CM LINK

DIMENSIONS



MAXIMUM CONNECTIONS

