



Head Office

40 Biloela Street
Villawood NSW 2163
T +612 9723 3099
F +612 9724 1899

Victoria

46-48 Keys Road
Moorabbin VIC 3189
T +613 9532 3168
F +613 9532 1838

Queensland

13/258 Musgrave Road
Coopers Plains QLD 4108
T +617 3276 8897
F +617 3277 8817

WA Agencies

Delta Lighting System
15 Hunt St. Malaga WA 6090
T +618 9249 4447
F +618 9249 2776



SL9721


KEW LED

LED BATTEN LIGHT

IP65



DIMENSIONS



FEATURES

- Round shape design vandal proof
- Polycarbonate body & diffuser
- Stainless steel clips & screws
- Built-in high efficiency SMD LED chips
- Constant current LED driver fitted
- Variable wattage, switch between 10/20W, 18/35W
- IP65 weatherproof

OPTIONS

DIMMING OPTIONS

- Analogue dimming (trailing edge, 1-10V)
- Digital dimming (DSI, DALI)
- Emergency, compliant to AS2293

ACCESSORIES INCLUDED

- Allen key & screws
- 20 mm cable glands
- Suspension brackets

INSTALLATION TYPE

- Surface mounted
- Suspended (Suspension Kit is required)

AVAILABLE

AVAILABLE COLOUR TEMPERATURE

- 3000K WARM WHITE
- 5000K DAYLIGHT

TECHNICAL SPECIFICATIONS

Model No.	Input Voltage	Power	Luminous Flux	Beam Angle	Colour Temp	CRI (Ra)	Dimmable	Dimensions L x W x H	Fitting Colour
SL9721/20W WW	240V~50Hz	10W/20W	800lm/1500lm	100°	3000K	>80	No	610 x 115 x 75 mm	White
SL9721/20W DL	240V~50Hz	10W/20W	800lm/1500lm	100°	5000K	>80	No	610 x 115 x 75 mm	White
SL9721/35W WW	240V~50Hz	18W/35W	1500lm/3000lm	100°	3000K	>80	No	1210 x 115 x 75 mm	White
SL9721/35W DL	240V~50Hz	18W/35W	1500lm/3000lm	100°	5000K	>80	No	1210 x 115 x 75 mm	White