

ECOLINE SL9732

LED narrow diffused batten with selectable colour

Application

Conventional linear LED batten products for commercial service spaces

Design Specifications

- 65 mm narrow steel body
- Quality white powder coat finish with robust polycarbonate diffuser
- Large terminal block, easy installation
- Easy selectable colour temperature with an inbuilt DIP switch 3000, 4000, 5700K
- High efficiency SMD LED chips, CRI > 80 120 degree beam distribution
- Integral constant current non-dimmable LED driver 20 and 40 watt models



Technical Specification

Model No.	Description	Input (V)	Power (W)	Lumens (lm)	CCT (K)	CRI
SL9732/20DL	LED DIFFUSED BATTEN 65X600 6K	240	20	1900	5700	80
SL9732/20EM	LED EMG DIFFUSED BAT 600x65mm	240	20			
SL9732/40DL	LED DIFFUSED BATTEN 65X1140 6K	240	40	3800	5700	80
SL9732/40CW	LED DIFFUSED BATTEN 65X1140 4K	240	40	3800	4000	80
SL9732/20TC	LED DIFFUSED BAT 600mm 3/4/6K	240	20	1900	3000/4000/5700	80
SL9732/40TC	LED DIFFUSED BAT 1140mm 3/4/6K	240	40	3800	3000/4000/5700	80

Model No.	Body Colour
SL9732/20DL	WHITE
SL9732/20EM	
SL9732/40DL	WHITE
SL9732/40CW	WHITE
SL9732/20TC	WHITE
SL9732/40TC	WHITE

Dimensions

SL9732 40

