



## FLEXI FLL2406/SS10

Dimmable 24V low voltage LED strip with silicon spray coating, IP65

### Application

An creative solution for residential and commercial interior and exterior spaces

### Design Specifications

- High efficiency SMD LED chips with 3M self-adhesive tape, 6 watt p/m, 550lm/m
- Roll length 20 m, cuttable every 100 mm at scissors symbol ✂
- Connection length can be extended with approved LED drivers, controllers and repeaters
- Dimmable with compatible controller or dimmable constant voltage LED driver. Dimming options -  
Type A - trailing edge dimmer  
Type B - LED Controller: LT8903DIM , LT8905DIM and LT8904DIM/RP  
Type C - 1-10V analogue
- Heat sink and 24V constant voltage LED driver required - LED CHANNEL OPTIONS SLT1000, SLT3000, SLT3010, SLT3020, SLT3030, SLT3040, SLT3050, SLT4050, SLT5000, Quick connect kit FLC10CS Twin 400 mm fly lead to connect 10 mm strip (pack of 10)
- SAL heatsink recommended (FLL2406/SS10)



### Technical Specification

Model No.	Description	Input (V)	CCT (K)	CRI	Body Colour
FLL2406WW/SS10	LED STRIP 24V 6W/m IP65 3K	24V DC	3000	80	CLEAR
FLL2406CW/SS10	LED STRIP 24V 6W/m IP65 4K	24V DC	4000	80	CLEAR
FLL2406DL/SS10	LED STRIP 24V 6W/m IP65 6K	24V DC	6000	80	CLEAR