



OPAL II SO3800 TC

30 watt commercial dimmable LED Oyster with selectable colour

Application

A perfect choice for apartments, residential or commercial spaces

Design Specifications

- Select colour temperature with DIP switch, 3000, 4000, 6000K,
- 30 watt integral constant current trailing edge dimmable LED driver (excluding SO3800/40TC/S, SO3800/40TC/EMS)
- Durable powder coated steel body profile, colour white
- Opal polycarbonate diffuser
- High efficiency SMD LED chips, CRI > 80
- Sensor models (SO3800/40TC/S, SO3800/40TC/EMS):

Performance

In Built Sensor - **YES**
Sensor Type - **MICRO**



Technical Specification

Model No.	Description	Input (V)	Power (W)	Lumens (lm)	CCT (K)	CRI
SO3800/40TC	LED OYSTER 30W 350mm 3/4/6K WH	240	30	2400/2600/2500	3000/4000/5700	80
SO3800/40TC/EM	LED OYST EMERG. 30W 3/4/6K WH	240	30	2400/2600/2500	3000/4000/5700	80
SO3800/40TC/EMS	LED OYST EM SENSOR 30W 3/4/6K	240	30	2400/2600/2500	3000/4000/5700	80
SO3800/40TC/S	LED OYST SENSOR 30W 3/4/6K WH	240	30	2400/2600/2500	3000/4000/5700	80

Model No.	Body Colour
SO3800/40TC	WHITE
SO3800/40TC/EM	WHITE
SO3800/40TC/EMS	WHITE
SO3800/40TC/S	WHITE

Dimensions

SO3800/40

