

**Head Office**

40 Biloela Street
Villawood NSW 2163
T +612 9723 3099
F +612 9724 1899

Victoria

46-48 Keys Road
Moorabbin VIC 3189
T +613 9532 3168
F +613 9532 1838

Queensland

13/258 Musgrave Road
Coopers Plains QLD 4108
T +617 3276 8897
F +617 3277 8817

WA Agencies

Delta Lighting System
15 Hunt St. Malaga WA 6090
T +618 9249 4447
F +618 9249 2776



SL9721/20EM




KEW LED EMERGENCY

LED BATTEN LIGHT EMERGENCY

SL9721/20EM



DIMENSIONS



EMERGENCY FEATURES

- Compliant to AS2293
- Emergency classification:
D50@C0, C180
D25@C90, C270
- LED charge status indicator
- Test switch with self-test function
- 3 hours emergency operation
- Intelligent automatic recharging function
- 16 hours charge time
- Deep discharge protection
- SELV classified

AVAILABLE COLOUR TEMPERATURE

- 3000K WARM WHITE
- 5000K DAYLIGHT

SL9721 FEATURES

- Round shape design vandal proof
- Polycarbonate body & diffuser
- Stainless steel clips & screws
- Built-in high efficiency SMD LED chips
- Constant current LED driver fitted
- IP65 weatherproof

INSTALLATION TYPE

- Surface mounted
- Suspended
(Suspension Kit is required)

ACCESSORIES INCLUDED

- Allen key & screws
- 20 mm cable glands
- Suspension brackets

EMERGENCY SPECIFICATIONS

Model No.	Input Voltage	Power	Luminous Flux	Beam Angle	Colour Temp	CRI (Ra)	Battery	Dimensions L x W x H	Battery Voltage	Fitting Colour
SL9721/20EM	240V~50Hz	3W	330lm	100°	3000K/5000K	>80	3000mAh	610 x 115 x 75 mm	3.6V	White