



SOL SL9726 TC

IP65 LED weatherproof batten with selectable colour

Application

Robust commercial or industrial utility choice, IP65 and IK08 rated

Design Specifications

- Colour temperature selectable by DIP switch, 3000 /4000 /6000K
- Rounded shape vandal proof design, robust polycarbonate body and UV stabilized polycarbonate diffuser
- Stainless steel clips & screws
- Built-in constant current non-dimmable LED driver
- Sensor, emergency, suspension kit options available
- Dimension: (LWH) 20 watt 642 x 118 x 77mm, 40 watt 1251 x 118 x 77mm

Performance

Dimmable Driver - **OPTIONAL**

In Built Sensor - **OPTIONAL**

Sensor Type - **MICRO**




Technical Specification

Model No.	Description	Input (V)	Power (W)	Lumens (lm)	CCT (K)	CRI
SL9726/20TC	LED BATTEN 642mm IP65 3/4/6K	240	20	1700/1800/1800	3000/4000/6000	80
SL9726/40TC	LED BATTEN 1251mm IP65 3/4/6K	240	40	3400/3600/3600	3000/4000/6000	80
SL9726/20TC/EM	LED VANDALPROOF 20W TC IP65 EM	240	20			80
SL9726/40TC/EM	LED VANDALPROOF 40W TC IP65 EM	240	40			80

Model No.	Body Colour
SL9726/20TC	GREY
SL9726/40TC	GREY
SL9726/20TC/EM	GREY
SL9726/40TC/EM	GREY

Dimensions

SL9726 (642 x 118 x 77mm),
(1251 x 118 x 77mm)



Product Images

