



Main

Commercial Status	Commercialised
Contactor application	Motor-heating-lighting
Range of product	ICT
Product or component type	Contactor
Device short name	ICT
Poles description	1P
Pole contact composition	1 NO
Network type	AC
Utilisation category	AC-7B conforming to IEC 1095 AC-7B conforming to EN 61095 AC-7A conforming to IEC 1095 AC-7A conforming to EN 61095 AC-5B conforming to EN 60947-4-1 AC-5A conforming to EN 60947-4-1 AC-3 conforming to EN 60947-4-1 AC-1 conforming to EN 60947-4-1
Control type	Remote control
Control circuit voltage	230/240 V AC 50 Hz

Complementary

[Ie] rated operational current	8.5 A AC-7B 25 A AC-7A
Network frequency	50/60 Hz
[Ue] rated operational voltage	250 V AC 50 Hz
Maximum power	3 kW 250 V AC
[Ui] rated insulation voltage	500 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	4 kV
Control signal type	Maintained
Switching frequency	100 switching operations/day
Local signalling	Action indicator
Hold-in power consumption VA	2.7 VA
Inrush power in VA	9.2 VA
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	60 mm
Colour	White
Electrical durability	200000 cycles AC 50/60 Hz conforming to IEC 1095 200000 cycles AC 50/60 Hz conforming to EN 61095
Connections - terminals	Control circuit: 2 tunnel type terminals 1.5 mm² for rigid cable(s) Control circuit: 2 tunnel type terminals 2.5 mm² for flexible cable(s) Power circuit: 1 tunnel type terminals 6 mm² for rigid cable(s) Power circuit: 2 tunnel type terminals 2.5 mm² for flexible cable(s)
Tightening torque	Power circuit: 1.2 N.m Control circuit: 0.8 N.m
Product compatibility	IACtc IACtp IACts IATEt

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	EN 61095 IEC 1095
Noise level	30 dB
Heat dissipation	0.9 W
IP degree of protection	IP20
Pollution degree	2
Tropicalisation	2 conforming to IEC 1095 2 conforming to EN 61095 2 conforming to EN 60947-4-1
Relative humidity	95 % 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-40...70 °C

RoHS compliance

RoHS EUR status	Compliant
RoHS EUR conformity date(YYWW)	1001

Contractual warranty

Period	18 months
--------	-----------