

### Main

Range of product	IIL
Device short name	IIL
Light source	LED
Cap/Operator or lens colour	Red
[Us] rated supply voltage	110...230 V AC 50/60 Hz

### Complementary

Switching frequency	2 Hz
Bulb lifespan	100000 h
Local signalling	1 blinker
Power consumption	0.3 W
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
Comb busbar distribution block compatibility	Upside: ProDis
9 mm pitches	2
Height	82 mm
Width	18 mm
Depth	69.5 mm
Auxiliary connection terminal	Tunnel type terminal 2 cable(s) flexible 2.5 mm <sup>2</sup> with cable end Tunnel type terminal 2 cable(s) flexible 2.5 mm <sup>2</sup> without cable end Tunnel type terminal 2 cable(s) rigid 2.5 mm <sup>2</sup> with cable end Tunnel type terminal 2 cable(s) rigid 2.5 mm <sup>2</sup> without cable end

### Environment

Standards	IEC 60947-5-1
IP degree of protection	IP2 IPxx B
Pollution degree	3
Tropicalisation	2
Relative humidity	95 % ( 55 °C )
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...100 °C