



Main

Range	Clario Librio Prodis Acti 9
Range of product	Clario DPN Vigi DPN C120 Librio ProDis ID
Product or component type	Overvoltage release
Device short name	MSU
Control circuit voltage	230 V AC 50/60 Hz
Threshold tripping voltage	400 V 0.07...0.2 s 300 V 1...5 s 275 V 3...15 s 255 V 350 V 0.25...0.75 s
9 mm pitches	2
Product compatibility	IDc C120 C60 C40 ITG40 IDPN ID C40 DPN Vigi DT40

Complementary

Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Colour	White
Connections - terminals	Clamp terminal 1 cable(s) 0.5...4 mm ² flexible Clamp terminal 1...6 mm ² rigid
Wire stripping length	10 mm
Tightening torque	1 N.m
Market segment	Residential Small commercial

Environment

Standards	EN 50550
Quality labels	CE
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available End Of Life Manual
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------