



Main

Range	Acti 9 Clario Librio Prodis
Range of product	Librio ProDis DPN Clario ID C120 DPN Vigi C60
Product or component type	Undervoltage release
Device short name	MNs
Control circuit voltage	220...240 V AC 50/60 Hz
Control type	Delayed
9 mm pitches	2
Product compatibility	ITG40 ID C40 DT60 IDc DPN Vigi IDPN C60 C120 DT40 C40

Complementary

Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Colour	White
Connections - terminals	Clamp terminal 2 cable(s) 1.5 mm ² rigid Clamp terminal 2 cable(s) 1.5 mm ² flexible Clamp terminal 1 cable(s) 2.5 mm ² flexible Clamp terminal 1 cable(s) 2.5 mm ² rigid
Wire stripping length	9 mm
Tightening torque	1 N.m
Market segment	Residential Small commercial

Environment

Standards	EN/IEC 60947-5-1
Product certifications	LCIE KEMA ASEFA ASTA
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available End Of Life Manual
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------