



Main

Range	Clario Acti 9 Prodis Librio
Range of product	ProDis ID DPN Vigi Librio C60 Clario DPN C120
Product or component type	Undervoltage release
Device short name	MNx
Control circuit voltage	400 V AC 50/60 Hz
Control type	With external feeding
9 mm pitches	2
Product compatibility	C120 DT60 IDc DT40 ID C40 ITG40 C40 IDPN C60 DPN Vigi

Complementary

Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Colour	White
Connections - terminals	Clamp terminal 1 cable(s) 2.5 mm ² flexible
Wire stripping length	9 mm
Tightening torque	1 N.m
Market segment	Residential Small commercial

Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASEFA ASTA KEMA LCIE
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available End Of Life Manual
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------