

# Product datasheet

Specifications



## Changeover switch, Acti9, 2P, 40A, 400/415VAC

A9SCO240

### Main

Range	Acti9
Product name	Acti9 iSSW
Product or component type	Changeover switch
Device short name	iSSW
Device application	Change source of supply
poles description	2P
Contacts type and composition	2 C/O
[Ie] rated operational current	40 A
[Ue] rated operational voltage	400/415 V
network type	AC
Network frequency	50/60 Hz
Utilisation category	AC-23A AC-22A

### Complementary

[Ui] rated insulation voltage	690 V
[Uimp] rated impulse withstand voltage	6 kV
[Icm] peak rated short-circuit making capacity	0.8 kA
[Icw] rated short-time withstand current	0.8 kA during 1 s at 400/415 V
Rated operational power in W	5 kW at 240 V (AC-23A) 4.8 kW at 230 V (AC-23A) 7.7 kW at 240 V (AC-22A) 7.4 kW at 230 V (AC-22A)
Control type	Toggle 3 positions
Mounting support	35 mm DIN rail
Mounting position	Vertical Any position
Locking options description	Padlock in ON position
Connections - terminals	Screw terminals (top and bottom) 1...10 mm <sup>2</sup> flexible Screw terminals (top and bottom) 1...10 mm <sup>2</sup> flexible with ferrule Screw terminals (top and bottom) 1...16 mm <sup>2</sup> rigid
Wire stripping length	12 mm for top and bottom connection
Tightening torque	2.5 N.m top and bottom
Suitability for isolation	Yes

Contact position indicator	Yes
Electrical durability	7000 cycles
Mechanical durability	10000 cycles
9 mm pitches	4
Height	85 mm
Width	35 mm
Depth	44 mm
Net weight	166 g

## Environment

Standards	EN/IEC 60947-3 AS/NZS 60947-3
Quality labels	CE RCM
IP degree of protection	IP20 IP40 inside enclosure
Pollution degree	3
Ambient air temperature for operation	-25...60 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.800 cm
Package 1 Width	8.100 cm
Package 1 Length	10.700 cm
Package 1 Weight	202.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	45
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	10.205 kg

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

RoHS Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu RoHS Directive Compliant  
[EU RoHS Declaration](#)

China RoHS Regulation [China RoHS declaration](#)  
Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations