

Main

Range	Linergy
Product name	FH
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	2P
Number of ways	12 ways, type : 2 L with 18 mm pitch
Distance between way	36 mm
Poles distribution	N L
Connector type	Tooth
Length in 18 mm mod- ules	24

Complementary

Device presentation	Cuttable	
[ln] rated current	100 A (40 °C)	
[Ue] rated operational voltage	415 V AC	
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2	
Mounting mode	Horizontal	
9 mm pitches	48	
Width	430 mm	
Colour	Anthracite grey (RAL 7016)	
Range compatibility	Acti 9	
Product compatibility	IC60 IID ISW-NA IK60 IID K ISW switch disconnector	

Environment

Standards	IEC 60947-7-1 IEC 61439-2
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1336 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold

Contractual warranty

	,
Deview	40 months
Period	18 MONTHS