



## Main

Range	Linergy
Product name	FH
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	3P
Number of ways	4 ways, type : 3 L with 18 mm pitch
Distance between way	54 mm
Poles distribution	L1 L2 L3
Connector type	Tooth
Length in 18 mm modules	12

## Complementary

Device presentation	Cuttable
[In] rated current	100 A ( 40 °C )
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V AC conforming to IEC 61439-2
Mounting mode	Horizontal
9 mm pitches	24
Width	220 mm
Colour	Anthracite grey ( RAL 7016 )
Range compatibility	Acti 9
Product compatibility	IC60 IID ISW-NA IK60 IID K ISW switch disconnecter

## Environment

Standards	IEC 60947-7-1 IEC 61439-2
Fire resistance	960 °C ( 30 s ) conforming to IEC 60695-2-1

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1336 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold

## Contractual warranty

Period	18 months
--------	-----------