



Main

| | |
|-------------------------------------|---|
| Range | Acti9 |
| Product name | Acti9 iID |
| Product or component type | Residual current circuit breaker (RCCB) |
| Device short name | IID |
| Device application | Electrical Vehicle charger |
| Poles description | 4P |
| Neutral position | Left |
| [In] rated current | 40 A |
| Network type | AC |
| Earth-leakage sensitivity | 30 mA |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type B-EV (Electric Vehicle) |
| Quality labels | VDE NF IMQ KEMA |

Complementary

| | |
|---|-------------------------------------|
| Device location in system | Outgoer Group incomer |
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 400 V AC 50 Hz |
| Rated breaking and making capacity | Idm 1500 A Im 1500 A |
| Rated conditional short-circuit current | 10 kA |
| [Ui] rated insulation voltage | 500 V |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Contact position indicator | Yes |
| Control type | Toggle |
| Local signalling | Trip indicator ON/OFF indication |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| 9 mm pitches | 8 |
| Height | 88 mm |
| Width | 72 mm |
| Depth | 79 mm |

| | |
|-----------------------------|---|
| Net weight | 415 G |
| Colour | White |
| Mechanical durability | 20000 Cycles |
| Electrical durability | 15000 Cycles |
| Locking options description | Padlocking device |
| Connections - terminals | Double terminal front 1...35 mm ² rigid Double terminal front 1...25 mm ² flexible Double terminal front 1...25 mm ² flexible with ferrule Double terminal back 1...25 mm ² rigid Double terminal back 1...16 mm ² flexible Double terminal back 1...16 mm ² flexible with ferrule |
| Wire stripping length | 14 Mm for top or bottom connection |
| Tightening torque | 3.5 N.M top or bottom |





Environment

| | |
|---------------------------------------|--|
| Standards | IEC 61008-2-1 IEC/EN 62423 EN 61008-2-1 |
| Product certifications | CCC KC |
| IP degree of protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| IK degree of protection | IK05 |
| Pollution degree | 3 |
| Overvoltage category | IV |
| Electromagnetic compatibility | 8/20 µs impulse withstand, 3 kA conforming to EN/IEC 61008-1 |
| Operating altitude | 0...2000 m |
| Ambient air temperature for operation | -25...60 °C |
| Ambient air temperature for storage | -40...85 °C |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 448 G |
| Package 1 Height | 7.5 Cm |
| Package 1 width | 8.5 Cm |
| Package 1 Length | 10 Cm |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 27 |
| Package 2 Weight | 12.55 Kg |
| Package 2 Height | 30 Cm |
| Package 2 width | 30 Cm |
| Package 2 Length | 40 Cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |

Circularity Profile

 [End Of Life Information](#)

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

| |
|---|
| Product Life Status : Commercialised |
|---|