



Main

Product name	Easy56
Product or component type	Switch and socket-outlet
Device short name	EY56C510
Plug, socket category	Low voltage
Poles description	3P + N + E
Control type	Rotary knob
Rotary handle padlocking	2 padlocks x Ø 8 mm
Network type	AC
Outlet standard	Australian/New Zealand

Complementary

Mounting mode	Surface mounted
Plug, socket, control station shape	Straight
[In] rated current	10 A
Pin number	5 pins
Shape of pin	Tubular
[Ue] rated operational voltage	500 V
Network frequency	50 Hz
Protection type	Without protection
Material	Polycarbonate
Contacts material	Brass pins :
Connections - terminals	Screw terminals
Cable cross section	1...16 mm ²
Cable entry number	1 x M32 2 x M25
Product weight	0.82 kg
Height	203 mm
Width	101 mm
Depth	101 mm
Colour	Dark grey rotary handle Grey RAL 7035 body
Targeted country	Australia New Zealand
Market segment	Small commercial Utility Industry

Environment

Standards	AS/NZS 3123 AS/NZS 3133
IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-25...75 °C
Ambient air temperature for storage	-25...75 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------